

Package ‘ggblanket’

July 22, 2025

Title Simplify 'ggplot2' Visualisation

Version 12.4.0

Description Simplify 'ggplot2' visualisation with 'ggblanket' wrapper functions.

License MIT + file LICENSE

URL <https://davidhodge931.github.io/ggblanket/>,
<https://github.com/davidhodge931/ggblanket>

BugReports <https://github.com/davidhodge931/ggblanket/issues>

Depends R (>= 4.2.0)

Imports colorspace, dplyr (>= 1.0.4), farver, forcats, ggblend, ggplot2 (>= 3.5.2), grid, hms (>= 0.5.0), labelled, lubridate (>= 1.7.8), purrr, rlang (>= 1.1.0), scales (>= 1.3.0), snakecase, stringr (>= 1.3.0), tidyr (>= 1.0.0), tidyselect (>= 1.2.0), viridisLite

Suggests spelling, hexbin, isoband, knitr, palmerpenguins, patchwork, quantreg, rmarkdown, sf, testthat (>= 3.0.0), tibble, vdiff, viridis

VignetteBuilder knitr

Config/Needs/website concaveman, corrr, farver, ggbeeswarm, ggblend, ggdensity, ggdist, ggeasy, ggforce, ggh4x, gghighlight, ggnewscale, ggrepel, ggridges, ggpattern, glue, marquee, paletteer, showtext, sysfonts

Config/testthat/edition 3

Encoding UTF-8

Language en-GB

RoxygenNote 7.3.2

NeedsCompilation no

Author David Hodge [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0002-3868-7501>>)

Maintainer David Hodge <davidhodge931@gmail.com>

Repository CRAN

Date/Publication 2025-06-03 04:20:02 UTC

Contents

aes_contrast	3
annotate_axis_line	4
bind_each_all	6
blue	7
dark_mode_r	8
gg_area	11
gg_bar	16
gg_bin_2d	20
gg_blanket	24
gg_boxplot	29
gg_col	33
gg_contour	38
gg_contour_filled	42
gg_crossbar	46
gg_density	51
gg_density_2d	55
gg_density_2d_filled	59
gg_errorbar	64
gg_freqpoly	68
gg_function	73
gg_hex	77
gg_histogram	81
gg_jitter	86
gg_label	90
gg_line	95
gg_linerange	99
gg_path	103
gg_point	108
gg_pointrange	112
gg_polygon	117
gg_qq	121
gg_quantile	126
gg_raster	130
gg_rect	134
gg_ribbon	139
gg_rug	143
gg_segment	148
gg_sf	152
gg_smooth	156
gg_step	161
gg_text	165
gg_tile	170

gg_violin	174
grey	178
guides_shape_grey	179
jumble	180
label_every_nth	181
lightness	182
light_mode_r	182
scale_x_symmetric	185
scale_y_symmetric	187
set_blanket	188

Index**191**

aes_contrast	<i>A colour aesthetic for contrast</i>
--------------	--

Description

A colour aesthetic to contrast with a fill aesthetic. Can be spliced into `ggplot2::aes` with `rlang::!!!`.

Usage

```
aes_contrast(..., dark = "#121B24FF", light = "#FFFFFFF")
```

Arguments

...	Provided to require argument naming, support trailing commas etc.
dark	A dark colour.
light	A light colour.

Value

A ggplot2 aesthetic

Examples

```
library(ggplot2)
library(dplyr)
library(stringr)
library(palmerpenguins)

set_blanket()

penguins |>
  count(species, sex) |>
  gg_col(
    x = sex,
    y = n,
    col = species,
```

```

    label = n,
    position = position_dodge(preserve = "single"),
    width = 0.75,
    x_labels = \(x) str_to_sentence(x),
  ) +
  geom_text(
    mapping = aes_contrast(),
    position = position_dodge(width = 0.75, preserve = "single"),
    vjust = 1.33,
    show.legend = FALSE,
  )

penguins |>
  count(species, sex) |>
  gg_col(
    x = sex,
    y = n,
    col = species,
    position = position_dodge(preserve = "single"),
    width = 0.75,
    x_labels = \(x) str_to_sentence(x),
    theme = dark_mode_r(),
  ) +
  geom_text(
    mapping = aes(label = n, !!!aes_contrast(dark = darkness[3], light = darkness[1])),
    position = position_dodge(width = 0.75, preserve = "single"),
    vjust = 1.33,
    show.legend = FALSE,
  )

```

annotate_axis_line *Annotated axis line segment*

Description

Replace a axis line with an annotated segment, so that geom features are in front of it.

Usage

```

annotate_axis_line(
  axis = "x",
  ...,
  x_position = "bottom",
  y_position = "left",
  colour = NULL,
  linewidth = NULL
)

```

Arguments

axis	The axis. Either "x" or "y"
...	Extra parameters passed to <code>ggplot2::annotate("segment", ...)</code> .
x_position	The position of the "x" axis, if applicable. Either "bottom" or "top".
y_position	The position of the "y" axis, if applicable. Either "left" or "right".
colour	The colour of the annotated segment.
linewidth	The linewidth of the annotated segment.

Value

A list of a annotate layer and theme elements.

Examples

```
library(dplyr)
library(ggplot2)
library(ggblanket)
library(palmerpenguins)

set_blanket()

d <- penguins |>
  add_row(
    flipper_length_mm = 175,
    body_mass_g = 2500,
    species = "Adelie",
  )

# axis line goes through geom
d |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
  )

# axis line does not go through geom
d |>
  gg_blanket(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
  ) +
  annotate_axis_line() +
  geom_point()
```

bind_each_all	<i>Bind each all.</i>
---------------	-----------------------

Description

Binds data to support plotting each category *and* all combined data.

Usage

```
bind_each_all(  
  data,  
  ...,  
  name = "each_all",  
  each = "Each",  
  all = "All",  
  all_after = Inf  
)
```

Arguments

data	A data frame or tibble.
...	An unquoted variable.
name	A variable name. Defaults to each_all.
each	A string for the each value. Defaults to "Each".
all	A string for the all value. Defaults to "All".
all_after	A number for where the all value should be placed after. Use 0 for first or Inf for last. Defaults to Inf.

Value

A data frame or tibble

Examples

```
library(dplyr)  
library(ggplot2)  
library(palmerpenguins)  
  
set_blanket()  
  
penguins |>  
  distinct(species)  
  
penguins |>  
  bind_each_all(species) |>  
  distinct(species, each_all)
```

```
penguins |>
  bind_each_all(species) |>
  gg_jitter(
    x = species,
    y = body_mass_g,
  )

penguins |>
  bind_each_all(species) |>
  gg_jitter(
    x = species,
    y = body_mass_g,
    col = each_all,
    col_palette = c(blue, grey),
  ) +
  theme(legend.position = "none")

penguins |>
  bind_each_all(species) |>
  group_by(species, each_all) |>
  summarise(across(body_mass_g, \(x) mean(x, na.rm = TRUE))) |>
  gg_col(
    x = species,
    y = body_mass_g,
    col = each_all,
    col_palette = c(blue, grey),
    width = 0.5,
    y_label = "Average body mass g",
  ) +
  theme(legend.position = "none")

penguins |>
  bind_each_all(species, all = "All\nspecies") |>
  gg_jitter(
    x = species,
    y = body_mass_g,
    col = each_all,
    col_palette = c(blue, grey),
    facet = each_all,
    facet_layout = "grid",
    facet_scales = "free_x",
    facet_space = "free_x",
  ) +
  theme(legend.position = "none") +
  theme(strip.text.x = element_blank()) +
  labs(x = NULL)
```

Description

A blue colour.

Usage

```
blue
```

Value

A character vector.

Examples

```
scales::show_col(blue)
```

dark_mode_r

Dark mode theme family

Description

A dark mode family of functions:

- `dark_mode_r()` with legend on right
- `dark_mode_t()` with legend on top
- `dark_mode_b()` with legend on bottom

Usage

```
dark_mode_r(
  ...,
  base_size = 11,
  base_family = "",
  base_colour = "#C8D7DFFF",
  axis_line_colour = "#C8D7DFFF",
  axis_line_linewidth = 0.25,
  axis_ticks_colour = axis_line_colour,
  axis_ticks_linewidth = axis_line_linewidth,
  axis_ticks_length = grid::unit(11/3, "pt"),
  panel_grid_colour = "#00040AFF",
  panel_grid_linewidth = 1.33,
  panel_background_fill = "#050D1BFF",
  plot_background_fill = "#00040AFF",
  legend_axis_line_colour = plot_background_fill,
  legend_axis_line_linewidth = axis_line_linewidth,
  legend_background_fill = plot_background_fill,
  legend_key_fill = plot_background_fill,
  legend_ticks_colour = legend_axis_line_colour,
```



```
    legend_ticks_linewidth = legend_axis_line_linewidth,
    legend_ticks_length = ggplot2::rel(c(0.175, 0))
  )

dark_mode_t(
  ...,
  base_size = 11,
  base_family = "",
  base_colour = "#C8D7DFFF",
  axis_line_colour = "#C8D7DFFF",
  axis_line_linewidth = 0.25,
  axis_ticks_colour = axis_line_colour,
  axis_ticks_linewidth = axis_line_linewidth,
  axis_ticks_length = grid::unit(11/3, "pt"),
  panel_grid_colour = "#00040AFF",
  panel_grid_linewidth = 1.33,
  panel_background_fill = "#050D1BFF",
  plot_background_fill = "#00040AFF",
  legend_axis_line_colour = plot_background_fill,
  legend_axis_line_linewidth = axis_line_linewidth,
  legend_background_fill = plot_background_fill,
  legend_key_fill = plot_background_fill,
  legend_ticks_colour = legend_axis_line_colour,
  legend_ticks_linewidth = legend_axis_line_linewidth,
  legend_ticks_length = ggplot2::rel(c(0.175, 0))
)

dark_mode_b(
  ...,
  base_size = 11,
  base_family = "",
  base_colour = "#C8D7DFFF",
  axis_line_colour = "#C8D7DFFF",
  axis_line_linewidth = 0.25,
  axis_ticks_colour = axis_line_colour,
  axis_ticks_linewidth = axis_line_linewidth,
  axis_ticks_length = grid::unit(11/3, "pt"),
  panel_grid_colour = "#00040AFF",
  panel_grid_linewidth = 1.33,
  panel_background_fill = "#050D1BFF",
  plot_background_fill = "#00040AFF",
  legend_axis_line_colour = plot_background_fill,
  legend_axis_line_linewidth = axis_line_linewidth,
  legend_background_fill = plot_background_fill,
  legend_key_fill = plot_background_fill,
  legend_ticks_colour = legend_axis_line_colour,
  legend_ticks_linewidth = legend_axis_line_linewidth,
  legend_ticks_length = ggplot2::rel(c(0.175, 0))
)
```

)

Arguments

...	Provided to require argument naming, support trailing commas etc.
base_size	The base size of the text theme element. Defaults to 11.
base_family	The base family of the text theme element. Defaults to "".
base_colour	The base colour of the text theme element.
axis_line_colour	The colour of the axis.line theme element.
axis_line_linewidth	The linewidth of the axis.line theme element.
axis_ticks_colour	The colour of the axis.ticks theme element.
axis_ticks_linewidth	The linewidth of the axis.ticks theme element.
axis_ticks_length	The length of the axis.ticks.length theme element.
panel_grid_colour	The colour of the panel.grid theme element.
panel_grid_linewidth	The linewidth of the panel.grid theme element.
panel_background_fill	The fill (and colour) of the panel.background theme element.
plot_background_fill	The fill (and colour) of the plot.background theme element.
legend_axis_line_colour	The colour of the legend.axis.line theme element.
legend_axis_line_linewidth	The linewidth of the legend.axis.line theme element.
legend_background_fill	The fill (and colour) of the legend.background theme element.
legend_key_fill	The fill (and colour) of the legend.key theme element.
legend_ticks_colour	The colour of the legend.ticks theme element.
legend_ticks_linewidth	The linewidth of the legend.ticks theme element.
legend_ticks_length	The theme element.

Value

A ggplot theme.legend.ticks.length

Examples

```
library(palmerpenguins)
library(ggplot2)

set_blanket()

penguins |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
    mode = dark_mode_r()
  )

penguins |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
    mode = dark_mode_t()
  )

penguins |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
    mode = dark_mode_b()
  )
```

gg_area

Area ggplot

Description

Create an area ggplot with a wrapper around `ggplot2::ggplot() + geom_area()`.

Usage

```
gg_area(
  data = NULL,
  ...,
  stat = "align",
  position = "stack",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
```

```
theme_axis_ticks_rm = NULL,  
theme_panel_grid_rm = NULL,  
blend = NULL,  
x = NULL,  
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,
```

```

col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in layer().
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. ggplot2::position_identity()).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. ggplot2::coord_cartesian()).
theme	A ggplot2 theme (e.g. light_mode_t() or dark_mode_r()). (Or a list that includes 1. a theme and 2. a ggplot2::labs() function. E.g. list(light_mode_r(), labs(colour = NU
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.

blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_prefix</code> (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a <code>scales::rescale()</code> function.

col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + *_theme_*() may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

economics |>
  gg_area(
    x = date,
    y = unemploy,
    y_label = "Unemployment",
  )
```

`gg_bar`*Bar ggplot*

Description

Create a bar ggplot with a wrapper around `ggplot2::ggplot() + geom_bar()`.

Usage

```
gg_bar(  
  data = NULL,  
  ...,  
  stat = "count",  
  position = "stack",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),
```



```

x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in layer().
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position sub-

	class object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. ggplot2::position_identity()).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. ggplot2::coord_cartesian()).
theme	A ggplot2 theme (e.g. light_mode_t() or dark_mode_r()). (Or a list that includes 1. a theme and 2. a ggplot2::labs() function. E.g. list(light_mode_r(), labs(colour = NU
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per ggblend::blend() (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in ggplot2::aes(). Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A scales::breaks_* function (e.g. scales::breaks_*()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when *_breaks = NULL.
x_expand, y_expand	Padding to the limits with the ggplot2::expansion() function, or a vector of length 2 (e.g. c(0, 0)).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with forcats::fct_expand.
x_label, y_label, col_label	Label for the axis or legend title. Use + ggplot2::labs(... = NULL) for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. \(\x\) stringr::str_to_sentence(x) or scales::label_*()), or a vector of labels. (Note this must be named for facet_labels).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using y_position = "top" with a *_theme_* theme, add caption = "" or caption = "\n".

<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. <code>"log10"</code>).
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> . Sometimes + <code>*_theme_*()</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> .
<code>facet_layout</code>	Whether the layout is to be <code>"wrap"</code> or <code>"grid"</code> . If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to <code>"wrap"</code> . If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to <code>"grid"</code> .
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of <code>"wrap"</code> .
<code>facet_scales</code>	Whether facet scales should be <code>"fixed"</code> across facets, <code>"free"</code> in both directions, or free in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>facet_space</code>	When the facet scales are <i>not</i> <code>"fixed"</code> , whether facet space should be <code>"fixed"</code> across facets, <code>"free"</code> to be proportional in both directions, or free to be proportional in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_bar(
    y = species,
    width = 0.75,
  )
```

gg_bin_2d

Bin_2d ggplot

Description

Create a bin2d ggplot with a wrapper around `ggplot2::ggplot() + geom_bin_2d()`.

Usage

```
gg_bin_2d(
  data = NULL,
  ...,
  stat = "bin2d",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
  yend = NULL,
  z = NULL,
  col = NULL,
  facet = NULL,
  facet2 = NULL,
```

```
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,  
facet_scales = "fixed",
```

```

facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .

<code>x_expand, y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".

facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

diamonds |>
  gg_bin_2d(
    x = carat,
    y = price,
  )
```

gg_blanket

Blanket ggplot

Description

Create a blanket ggplot with a wrapper around `ggplot2::ggplot() + layer()` with `geom_blank()` defaults. This function underlies all other `gg_*` functions. It contains a `geom` argument for maximum flexibility.

Usage

```
gg_blanket(
  data = NULL,
  ...,
  geom = "blank",
  stat = "identity",
  position = "identity",
  coord = NULL,
```



```
theme = NULL,  
theme_orientation = NULL,  
theme_axis_line_rm = NULL,  
theme_axis_ticks_rm = NULL,  
theme_panel_grid_rm = NULL,  
blend = NULL,  
x = NULL,  
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,
```

```

col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>geom</code>	A geometric object to display the data. A snakecase character string of a ggproto Geom subclass object minus the Geom prefix (e.g. "point").
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.

theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_prefix</code> (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.

<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> () may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol</code> , <code>facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>facet_space</code>	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_blanket(
    geom = "violin",
    stat = "ydensity",
    position = "dodge",
    x = species,
```

```
  y = body_mass_g,  
  col = sex,  
)
```

gg_boxplot

Boxplot ggplot

Description

Create a boxplot ggplot with a wrapper around `ggplot2::ggplot() + geom_boxplot()`.

Usage

```
gg_boxplot(  
  data = NULL,  
  ...,  
  stat = "boxplot",  
  position = "dodge2",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,
```

```
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,  
facet_scales = "fixed",  
facet_space = "fixed",  
title = NULL,  
subtitle = NULL,  
caption = NULL,  
label_case = NULL  
)
```

Arguments

data A data frame or tibble.

...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*</code> () function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
coord	A coordinate system. A <code>coord_*</code> () function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
theme	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.

<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_prefix</code> (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>facet_space</code>	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_boxplot(
    x = flipper_length_mm,
    y = species,
    col = sex,
    blend = "multiply",
  )
```

gg_col

Col ggplot

Description

Create a col ggplot with a wrapper around `ggplot2::ggplot() + geom_col()`.

Usage

```
gg_col(
  data = NULL,
  ...,
  stat = "identity",
  position = "stack",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
```

```
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,
```

```

facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*</code> () function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
coord	A coordinate system. A <code>coord_*</code> () function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
theme	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.

<code>x_breaks, y_breaks, col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
<code>x_breaks_n, y_breaks_n, col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand, y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> () may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".

facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  tidyr::drop_na(sex) |>
  group_by(sex, species) |>
  summarise(across(flipper_length_mm, \(x) mean(x, na.rm = TRUE))) |>
  gg_col(
    x = flipper_length_mm,
    y = species,
    col = sex,
    position = position_dodge(preserve = "single"),
    width = 0.75,
  )
```

`gg_contour`*Contour ggplot*

Description

Create a contour ggplot with a wrapper around `ggplot2::ggplot() + geom_contour()`.

Usage

```
gg_contour(  
  data = NULL,  
  ...,  
  stat = "contour",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),
```

```

x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position sub-

	class object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. ggplot2::position_identity()).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. ggplot2::coord_cartesian()).
theme	A ggplot2 theme (e.g. light_mode_t() or dark_mode_r()). (Or a list that includes 1. a theme and 2. a ggplot2::labs() function. E.g. list(light_mode_r(), labs(colour = NU
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per ggblend::blend() (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in ggplot2::aes(). Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A scales::breaks_* function (e.g. scales::breaks_*()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when *_breaks = NULL.
x_expand, y_expand	Padding to the limits with the ggplot2::expansion() function, or a vector of length 2 (e.g. c(0, 0)).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with forcats::fct_expand.
x_label, y_label, col_label	Label for the axis or legend title. Use + ggplot2::labs(... = NULL) for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. \(\x\) stringr::str_to_sentence(x) or scales::label_*()), or a vector of labels. (Note this must be named for facet_labels).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using y_position = "top" with a *_theme_* theme, add caption = "" or caption = "\n".

<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. <code>"log10"</code>).
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> . Sometimes + <code>*_theme_*()</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> .
<code>facet_layout</code>	Whether the layout is to be <code>"wrap"</code> or <code>"grid"</code> . If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to <code>"wrap"</code> . If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to <code>"grid"</code> .
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of <code>"wrap"</code> .
<code>facet_scales</code>	Whether facet scales should be <code>"fixed"</code> across facets, <code>"free"</code> in both directions, or free in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>facet_space</code>	When the facet scales are <i>not</i> <code>"fixed"</code> , whether facet space should be <code>"fixed"</code> across facets, <code>"free"</code> to be proportional in both directions, or free to be proportional in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

ggplot2::faithfuld |>
  gg_contour(
    x = waiting,
    y = eruptions,
    z = density,
  )
```

gg_contour_filled *Contour_filled ggplot*

Description

Create a contour_filled ggplot with a wrapper around `ggplot2::ggplot() + geom_contour_filled()`.

Usage

```
gg_contour_filled(
  data = NULL,
  ...,
  stat = "contour_filled",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
  yend = NULL,
  z = NULL,
  col = NULL,
  facet = NULL,
  facet2 = NULL,
```

```
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,  
facet_scales = "fixed",
```

```

facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .

x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a <code>scales::rescale()</code> function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".

facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

faithfuld |>
  gg_contour_filled(
    x = waiting,
    y = eruptions,
    z = density,
    bins = 8,
  )
```

 gg_crossbar

Crossbar ggplot

Description

Create a crossbar ggplot with a wrapper around `ggplot2::ggplot() + geom_crossbar()`.

Usage

```
gg_crossbar(
  data = NULL,
  ...,
  stat = "identity",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
```

```
theme_orientation = NULL,  
theme_axis_line_rm = NULL,  
theme_axis_ticks_rm = NULL,  
theme_panel_grid_rm = NULL,  
blend = NULL,  
x = NULL,  
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,
```

```

col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.

theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_ prefix</code> (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.

<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> () may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol</code> , <code>facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>facet_space</code>	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

data.frame(
  trt = factor(c(1, 1, 2, 2)),
  resp = c(1, 5, 3, 4),
  group = factor(c(1, 2, 1, 2)),
  upper = c(1.1, 5.3, 3.3, 4.2),
  lower = c(0.8, 4.6, 2.4, 3.6)
) |>
gg_crossbar(
  x = trt,
```

```
y = resp,  
ymin = lower,  
ymax = upper,  
col = group,  
width = 0.5,  
x_label = "Treatment",  
y_label = "Response",  
blend = "multiply",  
)
```

gg_density

Density ggplot

Description

Create a density ggplot with a wrapper around `ggplot2::ggplot() + geom_density()`.

Usage

```
gg_density(  
  data = NULL,  
  ...,  
  stat = "density",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,
```

```
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,  
facet_scales = "fixed",  
facet_space = "fixed",  
title = NULL,  
subtitle = NULL,  
caption = NULL,
```

```
  label_case = NULL
)
```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand</code> , <code>y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include</code> , <code>y_limits_include</code> , <code>col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .

<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_*</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>facet_space</code>	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".

title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_density(
    x = flipper_length_mm,
    col = species,
    blend = "multiply",
  )
```

gg_density_2d

Density_2d ggplot

Description

Create a density_2d ggplot with a wrapper around `ggplot2::ggplot() + geom_density_2d()`.

Usage

```
gg_density_2d(
  data = NULL,
  ...,
  stat = "density_2d",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
```

```
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,
```



```

col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.

mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a <code>scales::rescale()</code> function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> () may be needed.

facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

faithful |>
  gg_density_2d(
    x = waiting,
    y = eruptions,
    bins = 8,
    contour = TRUE,
  )
```

gg_density_2d_filled *Density_2d_filled ggplot*

Description

Create a density_2d_filled ggplot with a wrapper around `ggplot2::ggplot()` + `geom_density_2d_filled()`.

Usage

```
gg_density_2d_filled(  
  data = NULL,  
  ...,  
  stat = "density_2d_filled",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),  
  x_symmetric = NULL,  
  x_transform = NULL,  
  y_breaks = NULL,  
  y_breaks_n = NULL,  
  y_expand = NULL,  
  y_limits_include = NULL,  
  y_label = NULL,  
  y_labels = NULL,  
  y_position = "left",
```

```

y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
coord	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
theme	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".

theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").

col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a scales::pal_*() function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a scales::rescale() function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + *_theme_*() may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

faithful |>
```

```
gg_density_2d_filled(  
  x = waiting,  
  y = eruptions,  
  bins = 8,  
  contour = TRUE,  
)
```

gg_errorbar

Errorbar ggplot

Description

Create a errorbar ggplot with a wrapper around `ggplot2::ggplot() + geom_errorbar()`.

Usage

```
gg_errorbar(  
  data = NULL,  
  ...,  
  stat = "identity",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,
```



```
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,  
facet_scales = "fixed",  
facet_space = "fixed",  
title = NULL,  
subtitle = NULL,  
caption = NULL,  
label_case = NULL  
)
```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand</code> , <code>y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include</code> , <code>y_limits_include</code> , <code>col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label</code> , <code>y_label</code> , <code>col_label</code>	Label for the axis or legend title. Use + <code>ggplot2::labs(... = NULL)</code> for no title.

x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_*</code> prefix (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a <code>scales::rescale()</code> function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

data.frame(
  trt = factor(c(1, 1, 2, 2)),
  resp = c(1, 5, 3, 4),
  group = factor(c(1, 2, 1, 2)),
  upper = c(1.1, 5.3, 3.3, 4.2),
  lower = c(0.8, 4.6, 2.4, 3.6)
) |>
gg_errorbar(
  x = trt,
  ymin = lower,
  ymax = upper,
  col = group,
  width = 0.1,
  x_label = "Treatment",
  y_label = "Response",
)
```

 gg_freqpoly

Freqpoly ggplot

Description

Create a freqpoly ggplot with a wrapper around `ggplot2::ggplot() + geom_freqpoly()`.

Usage

```
gg_freqpoly(
  data = NULL,
  ...,
  stat = "bin",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
```

```
blend = NULL,  
x = NULL,  
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,
```

```

col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*</code> () function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*</code> () function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").

x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_*</code> prefix (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a <code>scales::rescale()</code> function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.

facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + *_theme_*() may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_freqpoly(
    x = flipper_length_mm,
    col = sex,
  )
```

gg_function	<i>Function ggplot</i>
-------------	------------------------

Description

Create a function `ggplot` with a wrapper around `ggplot2::ggplot()` + `geom_function()`.

Usage

```
gg_function(  
  data = NULL,  
  ...,  
  stat = "function",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),
```

```

x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position sub-

	class object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
theme	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when *_breaks = NULL.
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use + <code>ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for facet_labels).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a *_theme_* theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .

<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. <code>"log10"</code>).
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> . Sometimes + <code>*_theme_*()</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> .
<code>facet_layout</code>	Whether the layout is to be <code>"wrap"</code> or <code>"grid"</code> . If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to <code>"wrap"</code> . If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to <code>"grid"</code> .
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of <code>"wrap"</code> .
<code>facet_scales</code>	Whether facet scales should be <code>"fixed"</code> across facets, <code>"free"</code> in both directions, or free in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>facet_space</code>	When the facet scales are <i>not</i> <code>"fixed"</code> , whether facet space should be <code>"fixed"</code> across facets, <code>"free"</code> to be proportional in both directions, or free to be proportional in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

gg_function(
  fun = \(x) dnorm(x, mean = 0, sd = 5),
  x_limits_include = qnorm(p = c(0.005, 0.995), mean = 0, sd = 5),
  y_limits_include = 0,
)
```

gg_hex

Hex ggplot

Description

Create a hex ggplot with a wrapper around `ggplot2::ggplot() + geom_hex()`.

Usage

```
gg_hex(
  data = NULL,
  ...,
  stat = "binhex",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
  yend = NULL,
  z = NULL,
  col = NULL,
  facet = NULL,
  facet2 = NULL,
  group = NULL,
```

```
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,  
facet_scales = "fixed",  
facet_space = "fixed",
```

```

  title = NULL,
  subtitle = NULL,
  caption = NULL,
  label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand</code> , <code>y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).

<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".

facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

diamonds |>
  gg_hex(
    x = carat,
    y = price,
  )
```

gg_histogram

Histogram ggplot

Description

Create a histogram ggplot with a wrapper around `ggplot2::ggplot() + geom_histogram()`.

Usage

```
gg_histogram(
  data = NULL,
  ...,
  stat = "bin",
  position = "stack",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
```

```
blend = NULL,  
x = NULL,  
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,
```

```

col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*</code> () function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*</code> () function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").

x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_*</code> prefix (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a <code>scales::rescale()</code> function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.

facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + *_theme_*() may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_histogram(
    x = flipper_length_mm,
    col = sex,
    bins = 50,
  )
```

`gg_jitter`*Jitter ggplot*

Description

Create a jitter ggplot with a wrapper around `ggplot2::ggplot() + geom_jitter()`.

Usage

```
gg_jitter(  
  data = NULL,  
  ...,  
  stat = "identity",  
  position = "jitter",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),
```

```

x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position sub-

	class object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. ggplot2::position_identity()).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. ggplot2::coord_cartesian()).
theme	A ggplot2 theme (e.g. light_mode_t() or dark_mode_r()). (Or a list that includes 1. a theme and 2. a ggplot2::labs() function. E.g. list(light_mode_r(), labs(colour = NU
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per ggblend::blend() (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in ggplot2::aes(). Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A scales::breaks_* function (e.g. scales::breaks_*()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when *_breaks = NULL.
x_expand, y_expand	Padding to the limits with the ggplot2::expansion() function, or a vector of length 2 (e.g. c(0, 0)).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with forcats::fct_expand.
x_label, y_label, col_label	Label for the axis or legend title. Use + ggplot2::labs(... = NULL) for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. \(\x\) stringr::str_to_sentence(x) or scales::label_*()), or a vector of labels. (Note this must be named for facet_labels).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using y_position = "top" with a *_theme_* theme, add caption = "" or caption = "\n".

<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. <code>"log10"</code>).
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> . Sometimes + <code>*_theme_*()</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> .
<code>facet_layout</code>	Whether the layout is to be <code>"wrap"</code> or <code>"grid"</code> . If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to <code>"wrap"</code> . If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to <code>"grid"</code> .
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of <code>"wrap"</code> .
<code>facet_scales</code>	Whether facet scales should be <code>"fixed"</code> across facets, <code>"free"</code> in both directions, or free in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>facet_space</code>	When the facet scales are <i>not</i> <code>"fixed"</code> , whether facet space should be <code>"fixed"</code> across facets, <code>"free"</code> to be proportional in both directions, or free to be proportional in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

set.seed(123)

penguins |>
  gg_jitter(
    x = species,
    y = body_mass_g,
    col = flipper_length_mm,
    position = position_jitter(height = 0),
    y_limits_include = 0,
    col_steps = TRUE,
  )
```

`gg_label`*Label ggplot*

Description

Create a label ggplot with a wrapper around `ggplot2::ggplot() + geom_label()`.

Usage

```
gg_label(
  data = NULL,
  ...,
  stat = "identity",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
```

```
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,
```

```

facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.

x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a <code>scales::rescale()</code> function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> () may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".

facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

bind_rows(
  mtcars |> slice_min(order_by = mpg),
  mtcars |> slice_max(order_by = mpg)
) |>
tibble::rownames_to_column("themel") |>
gg_label(
  x = themel,
  y = mpg,
  label = themel,
  y_limits_include = 0,
  y_label = "Miles per gallon",
  col_palette = c(orange, "white", teal),
)
```

`gg_line`*Line ggplot*

Description

Create a line ggplot with a wrapper around `ggplot2::ggplot() + geom_line()`.

Usage

```
gg_line(  
  data = NULL,  
  ...,  
  stat = "identity",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),
```

```

x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position sub-

	class object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
theme	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when *_breaks = NULL.
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use + <code>ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a *_theme_* theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .

<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. <code>"log10"</code>).
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> . Sometimes + <code>*_theme_*()</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> .
<code>facet_layout</code>	Whether the layout is to be <code>"wrap"</code> or <code>"grid"</code> . If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to <code>"wrap"</code> . If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to <code>"grid"</code> .
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of <code>"wrap"</code> .
<code>facet_scales</code>	Whether facet scales should be <code>"fixed"</code> across facets, <code>"free"</code> in both directions, or free in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>facet_space</code>	When the facet scales are <i>not</i> <code>"fixed"</code> , whether facet space should be <code>"fixed"</code> across facets, <code>"free"</code> to be proportional in both directions, or free to be proportional in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

economics |>
  gg_line(
    x = date,
    y = unemploy,
    y_limits_include = 0,
    y_label = "Unemployment",
  )
```

gg_linerange

Linerange ggplot

Description

Create a linerange ggplot with a wrapper around `ggplot2::ggplot() + geom_linerange()`.

Usage

```
gg_linerange(
  data = NULL,
  ...,
  stat = "identity",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
  yend = NULL,
  z = NULL,
  col = NULL,
  facet = NULL,
```

```
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,
```

```

  facet_scales = "fixed",
  facet_space = "fixed",
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*</code> () function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
coord	A coordinate system. A <code>coord_*</code> () function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
theme	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .

<code>x_expand, y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".

facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

data.frame(
  trt = factor(c(1, 1, 2, 2)),
  resp = c(1, 5, 3, 4),
  group = factor(c(1, 2, 1, 2)),
  upper = c(1.1, 5.3, 3.3, 4.2),
  lower = c(0.8, 4.6, 2.4, 3.6)
) |>
gg_linerange(
  x = trt,
  ymin = lower,
  ymax = upper,
  col = group,
  position = position_dodge(width = 0.2),
  x_label = "Treatment",
  y_label = "Response",
)
```

gg_path

Path ggplot

Description

Create a path ggplot with a wrapper around `ggplot2::ggplot() + geom_path()`.

Usage

```
gg_path(  
  data = NULL,  
  ...,  
  stat = "identity",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),  
  x_symmetric = NULL,  
  x_transform = NULL,  
  y_breaks = NULL,  
  y_breaks_n = NULL,  
  y_expand = NULL,  
  y_limits_include = NULL,  
  y_label = NULL,  
  y_labels = NULL,  
  y_position = "left",
```



```

y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*</code> () function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*</code> () function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".

theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").

col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a scales::pal_*() function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a scales::rescale() function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + *_theme_*() may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

economics |>
  mutate(unemploy_rate = unemploy / pop) |>
```

```

gg_path(
  x = unemploy_rate,
  y = psavert,
  x_label = "Unemployment rate",
  y_limits_include = 0,
  y_label = "Personal savings rate",
)

```

gg_point

Point ggplot

Description

Create a point ggplot with a wrapper around `ggplot2::ggplot() + geom_point()`.

Usage

```

gg_point(
  data = NULL,
  ...,
  stat = "identity",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
  yend = NULL,
  z = NULL,
  col = NULL,
  facet = NULL,
  facet2 = NULL,
  group = NULL,
  subgroup = NULL,
  label = NULL,
  text = NULL,
  sample = NULL,
  mapping = NULL,
)

```

```
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,  
facet_scales = "fixed",  
facet_space = "fixed",  
title = NULL,  
subtitle = NULL,  
caption = NULL,  
label_case = NULL  
)
```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand</code> , <code>y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include</code> , <code>y_limits_include</code> , <code>col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label</code> , <code>y_label</code> , <code>col_label</code>	Label for the axis or legend title. Use + <code>ggplot2::labs(... = NULL)</code> for no title.

x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_*</code> prefix (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
col_palette	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a <code>scales::rescale()</code> function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
  )
```

gg_pointrange

Pointrange ggplot

Description

Create a pointrange ggplot with a wrapper around `ggplot2::ggplot() + geom_pointrange()`.

Usage

```
gg_pointrange(
  data = NULL,
  ...,
  stat = "identity",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
  yend = NULL,
```



```
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,
```

```

facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.

<code>x_breaks_n, y_breaks_n, col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand, y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".

facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

data.frame(
  trt = factor(c(1, 1, 2, 2)),
  resp = c(1, 5, 3, 4),
  group = factor(c(1, 2, 1, 2)),
  upper = c(1.1, 5.3, 3.3, 4.2),
  lower = c(0.8, 4.6, 2.4, 3.6)
) |>
gg_pointrange(
  x = trt,
  y = resp,
  col = group,
  ymin = lower,
  ymax = upper,
  position = position_dodge(width = 0.2),
  x_label = "Treatment",
  y_label = "Response",
)
```

`gg_polygon`*Polygon ggplot*

Description

Create a polygon ggplot with a wrapper around `ggplot2::ggplot() + geom_polygon()`.

Usage

```
gg_polygon(  
  data = NULL,  
  ...,  
  stat = "identity",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),
```

```

x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position sub-

	class object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. ggplot2::position_identity()).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. ggplot2::coord_cartesian()).
theme	A ggplot2 theme (e.g. light_mode_t() or dark_mode_r()). (Or a list that includes 1. a theme and 2. a ggplot2::labs() function. E.g. list(light_mode_r(), labs(colour = NU
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per ggblend::blend() (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in ggplot2::aes(). Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A scales::breaks_* function (e.g. scales::breaks_*()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when *_breaks = NULL.
x_expand, y_expand	Padding to the limits with the ggplot2::expansion() function, or a vector of length 2 (e.g. c(0, 0)).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with forcats::fct_expand.
x_label, y_label, col_label	Label for the axis or legend title. Use + ggplot2::labs(... = NULL) for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. \(\x\) stringr::str_to_sentence(x) or scales::label_*()), or a vector of labels. (Note this must be named for facet_labels).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using y_position = "top" with a *_theme_* theme, add caption = "" or caption = "\n".

<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. <code>"log10"</code>).
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> . Sometimes + <code>*_theme_*()</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> .
<code>facet_layout</code>	Whether the layout is to be <code>"wrap"</code> or <code>"grid"</code> . If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to <code>"wrap"</code> . If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to <code>"grid"</code> .
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of <code>"wrap"</code> .
<code>facet_scales</code>	Whether facet scales should be <code>"fixed"</code> across facets, <code>"free"</code> in both directions, or free in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>facet_space</code>	When the facet scales are <i>not</i> <code>"fixed"</code> , whether facet space should be <code>"fixed"</code> across facets, <code>"free"</code> to be proportional in both directions, or free to be proportional in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

ids <- factor(c("1.1", "2.1", "1.2", "2.2", "1.3", "2.3"))

values <- data.frame(
  id = ids,
  value = c(3, 3.1, 3.1, 3.2, 3.15, 3.5)
)

positions <- data.frame(
  id = rep(ids, each = 4),
  x = c(
    2, 1, 1.1, 2.2, 1, 0, 0.3, 1.1, 2.2, 1.1, 1.2, 2.5, 1.1, 0.3,
    0.5, 1.2, 2.5, 1.2, 1.3, 2.7, 1.2, 0.5, 0.6, 1.3
  ),
  y = c(
    -0.5, 0, 1, 0.5, 0, 0.5, 1.5, 1, 0.5, 1, 2.1, 1.7, 1, 1.5,
    2.2, 2.1, 1.7, 2.1, 3.2, 2.8, 2.1, 2.2, 3.3, 3.2
  )
)

datapoly <- merge(values, positions, by = c("id"))

datapoly |>
  gg_polygon(
    x = x,
    y = y,
    col = value,
    group = id,
  )
```

gg_qq

Qq ggplot

Description

Create a qq ggplot with a wrapper around `ggplot2::ggplot() + geom_qq()`.

Usage

```
gg_qq(
  data = NULL,
  ...,
  stat = "qq",
```

```
position = "identity",
coord = ggplot2::coord_cartesian(clip = "off"),
theme = NULL,
theme_orientation = NULL,
theme_axis_line_rm = NULL,
theme_axis_ticks_rm = NULL,
theme_panel_grid_rm = NULL,
blend = NULL,
x = NULL,
xmin = NULL,
xmax = NULL,
xend = NULL,
y = NULL,
ymin = NULL,
ymax = NULL,
yend = NULL,
z = NULL,
col = NULL,
facet = NULL,
facet2 = NULL,
group = NULL,
subgroup = NULL,
label = NULL,
text = NULL,
sample = NULL,
mapping = NULL,
x_breaks = NULL,
x_breaks_n = NULL,
x_expand = NULL,
x_limits_include = NULL,
x_label = NULL,
x_labels = NULL,
x_position = "bottom",
x_sec_axis = ggplot2::waiver(),
x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
```

```

col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.

<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand</code> , <code>y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include</code> , <code>y_limits_include</code> , <code>col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label</code> , <code>y_label</code> , <code>col_label</code>	Label for the axis or legend title. Use <code>+ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels</code> , <code>y_labels</code> , <code>col_labels</code> , <code>facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position</code> , <code>y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis</code> , <code>y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric</code> , <code>y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform</code> , <code>y_transform</code> , <code>col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_prefix</code> (e.g. "log10").
<code>col_drop</code> , <code>facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol</code> , <code>col_legend_nrow</code>	The number of columns and rows in a legend guide.

<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> () may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol</code> , <code>facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>facet_space</code>	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_qq(
    sample = body_mass_g,
    facet = species,
    coord = coord_cartesian(clip = "on"),
  ) +
  geom_qq_line()
```

`gg_quantile`*Quantile ggplot*

Description

Create an quantile ggplot with a wrapper around `ggplot2::ggplot()` + `geom_quantile()`.

Usage

```
gg_quantile(  
  data = NULL,  
  ...,  
  stat = "quantile",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),
```

```

x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position sub-

	class object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. ggplot2::position_identity()).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. ggplot2::coord_cartesian()).
theme	A ggplot2 theme (e.g. light_mode_t() or dark_mode_r()). (Or a list that includes 1. a theme and 2. a ggplot2::labs() function. E.g. list(light_mode_r(), labs(colour = NU
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per ggblend::blend() (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in ggplot2::aes(). Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A scales::breaks_* function (e.g. scales::breaks_*()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when *_breaks = NULL.
x_expand, y_expand	Padding to the limits with the ggplot2::expansion() function, or a vector of length 2 (e.g. c(0, 0)).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with forcats::fct_expand.
x_label, y_label, col_label	Label for the axis or legend title. Use + ggplot2::labs(... = NULL) for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. \(\x\) stringr::str_to_sentence(x) or scales::label_*()), or a vector of labels. (Note this must be named for facet_labels).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using y_position = "top" with a *_theme_* theme, add caption = "" or caption = "\n".

<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. <code>"log10"</code>).
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> . Sometimes + <code>*_theme_*()</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> .
<code>facet_layout</code>	Whether the layout is to be <code>"wrap"</code> or <code>"grid"</code> . If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to <code>"wrap"</code> . If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to <code>"grid"</code> .
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of <code>"wrap"</code> .
<code>facet_scales</code>	Whether facet scales should be <code>"fixed"</code> across facets, <code>"free"</code> in both directions, or free in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>facet_space</code>	When the facet scales are <i>not</i> <code>"fixed"</code> , whether facet space should be <code>"fixed"</code> across facets, <code>"free"</code> to be proportional in both directions, or free to be proportional in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
if (requireNamespace("quantreg", quietly = TRUE)) {  
  library(ggplot2)  
  library(palmerpenguins)  
  
  set_blanket()  
  
  penguins |>  
    gg_quantile(  
      x = flipper_length_mm,  
      y = body_mass_g,  
    )  
}
```

gg_raster

Raster ggplot

Description

Create a raster ggplot with a wrapper around `ggplot2::ggplot()` + `geom_raster()`.

Usage

```
gg_raster(  
  data = NULL,  
  ...,  
  stat = "identity",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,
```

```
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,
```

```

facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*</code> () function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*</code> () function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .

<code>x_expand, y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".

facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

faithfuld |>
  gg_raster(
    x = waiting,
    y = eruptions,
    col = density,
  )
```

 gg_rect

Rect ggplot

Description

Create a rect ggplot with a wrapper around `ggplot2::ggplot() + geom_rect()`.

Usage

```
gg_rect(
  data = NULL,
  ...,
  stat = "identity",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
```

```
theme_axis_line_rm = NULL,  
theme_axis_ticks_rm = NULL,  
theme_panel_grid_rm = NULL,  
blend = NULL,  
x = NULL,  
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,
```

```

col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.

theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.

<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> () may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol</code> , <code>facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>facet_space</code>	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

data.frame(
  x = rep(c(2, 5, 7, 9, 12), 2),
  y = rep(c(1, 2), each = 5),
  z = factor(c(rep(1:4, each = 2), 5, NA)),
  w = rep(diff(c(0, 4, 6, 8, 10, 14)), 2)
) |>
mutate(
  xmin = x - w / 2,
  xmax = x + w / 2,
```

```
    ymin = y,  
    ymax = y + 1  
  ) |>  
  gg_rect(  
    xmin = xmin,  
    xmax = xmax,  
    ymin = ymin,  
    ymax = ymax,  
    col = z,  
  )
```

gg_ribbon

Ribbon ggplot

Description

Create a ribbon ggplot with a wrapper around `ggplot2::ggplot() + geom_ribbon()`

Usage

```
gg_ribbon(  
  data = NULL,  
  ...,  
  stat = "identity",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,
```

```
text = NULL,
sample = NULL,
mapping = NULL,
x_breaks = NULL,
x_breaks_n = NULL,
x_expand = NULL,
x_limits_include = NULL,
x_label = NULL,
x_labels = NULL,
x_position = "bottom",
x_sec_axis = ggplot2::waiver(),
x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
```

```

caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
coord	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
theme	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).

<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".

facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

data.frame(year = 1875:1972, level = as.vector(LakeHuron)) |>
  mutate(level_min = level - 1, level_max = level + 1) |>
  gg_ribbon(
    x = year,
    ymin = level_min,
    ymax = level_max,
    x_labels = \(x) x,
  )
```

 gg_rug

Rug ggplot

Description

Create a rug ggplot with a wrapper around `ggplot2::ggplot()` + `geom_rug()`.

Usage

```
gg_rug(
  data = NULL,
  ...,
  stat = "identity",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
```

```
theme_axis_ticks_rm = NULL,  
theme_panel_grid_rm = NULL,  
blend = NULL,  
x = NULL,  
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,
```



```

col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.

<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand</code> , <code>y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include</code> , <code>y_limits_include</code> , <code>col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label</code> , <code>y_label</code> , <code>col_label</code>	Label for the axis or legend title. Use <code>+ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels</code> , <code>y_labels</code> , <code>col_labels</code> , <code>facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position</code> , <code>y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis</code> , <code>y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric</code> , <code>y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform</code> , <code>y_transform</code> , <code>col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_prefix</code> (e.g. "log10").
<code>col_drop</code> , <code>facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol</code> , <code>col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.

col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + *_theme_*() may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_rug(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
  )
```

`gg_segment`*Segment ggplot*

Description

Create a segment ggplot with a wrapper around `ggplot2::ggplot() + geom_segment()`.

Usage

```
gg_segment(  
  data = NULL,  
  ...,  
  stat = "identity",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,  
  x_expand = NULL,  
  x_limits_include = NULL,  
  x_label = NULL,  
  x_labels = NULL,  
  x_position = "bottom",  
  x_sec_axis = ggplot2::waiver(),
```

```

x_symmetric = NULL,
x_transform = NULL,
y_breaks = NULL,
y_breaks_n = NULL,
y_expand = NULL,
y_limits_include = NULL,
y_label = NULL,
y_labels = NULL,
y_position = "left",
y_sec_axis = ggplot2::waiver(),
y_symmetric = NULL,
y_transform = NULL,
col_breaks = NULL,
col_breaks_n = 5,
col_drop = FALSE,
col_limits_include = NULL,
col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in <code>layer()</code> .
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position sub-

	class object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. ggplot2::position_identity()).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. ggplot2::coord_cartesian()).
theme	A ggplot2 theme (e.g. light_mode_t() or dark_mode_r()). (Or a list that includes 1. a theme and 2. a ggplot2::labs() function. E.g. list(light_mode_r(), labs(colour = NU
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.
theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per ggblend::blend() (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in ggplot2::aes(). Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A scales::breaks_* function (e.g. scales::breaks_*()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when *_breaks = NULL.
x_expand, y_expand	Padding to the limits with the ggplot2::expansion() function, or a vector of length 2 (e.g. c(0, 0)).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with forcats::fct_expand.
x_label, y_label, col_label	Label for the axis or legend title. Use + ggplot2::labs(... = NULL) for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. \(\x\) stringr::str_to_sentence(x) or scales::label_*()), or a vector of labels. (Note this must be named for facet_labels).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using y_position = "top" with a *_theme_* theme, add caption = "" or caption = "\n".

<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. <code>"log10"</code>).
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> . Sometimes + <code>*_theme_*()</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with <code>"margins"</code> , <code>"all"</code> , <code>"all_x"</code> , or <code>"all_y"</code> .
<code>facet_layout</code>	Whether the layout is to be <code>"wrap"</code> or <code>"grid"</code> . If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to <code>"wrap"</code> . If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to <code>"grid"</code> .
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of <code>"wrap"</code> .
<code>facet_scales</code>	Whether facet scales should be <code>"fixed"</code> across facets, <code>"free"</code> in both directions, or free in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>facet_space</code>	When the facet scales are <i>not</i> <code>"fixed"</code> , whether facet space should be <code>"fixed"</code> across facets, <code>"free"</code> to be proportional in both directions, or free to be proportional in just one direction (i.e. <code>"free_x"</code> or <code>"free_y"</code>). Defaults to <code>"fixed"</code> .
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

data.frame(x1 = 2.62, x2 = 3.57, y1 = 21.0, y2 = 15.0) |>
  gg_segment(
    x = x1,
    xend = x2,
    y = y1,
    yend = y2,
  )
```

gg_sf

Sf ggplot

Description

Create a blank ggplot with a wrapper around `ggplot2::ggplot() + geom_sf()`.

Usage

```
gg_sf(
  data = NULL,
  ...,
  stat = "sf",
  position = "identity",
  coord = ggplot2::coord_sf(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
  yend = NULL,
  z = NULL,
  col = NULL,
  facet = NULL,
```



```
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,
```

```

facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*</code> () function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*</code> () function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .

<code>x_expand, y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".

facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

if (requireNamespace("sf", quietly = TRUE)) {
  sf::st_read(system.file("shape/nc.shp", package = "sf")) |>
  gg_sf(
    col = AREA,
  )
}
```

gg_smooth

Smooth ggplot

Description

Create a smooth ggplot with a wrapper around `ggplot2::ggplot()` + `geom_smooth()`.

Usage

```
gg_smooth(
  data = NULL,
  ...,
  stat = "smooth",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
```

```
theme_axis_line_rm = NULL,  
theme_axis_ticks_rm = NULL,  
theme_panel_grid_rm = NULL,  
blend = NULL,  
x = NULL,  
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,
```

```

col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.

theme_panel_grid_rm	TRUE or FALSE of whether to remove the relevant panel grid per the theme_orientation of the plot.
blend	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
x, xmin, xmax, xend, y, ymin, ymax, yend, z, col, facet, facet2, group, subgroup, label, text, sample	An unquoted aesthetic variable.
mapping	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. shape, linetype, linewidth, or size), but can also be used for delayed evaluation etc.
x_breaks, y_breaks, col_breaks	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
x_breaks_n, y_breaks_n, col_breaks_n	A number of desired breaks for when <code>*_breaks = NULL</code> .
x_expand, y_expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
x_limits_include, y_limits_include, col_limits_include	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
x_label, y_label, col_label	Label for the axis or legend title. Use <code>+ggplot2::labs(... = NULL)</code> for no title.
x_labels, y_labels, col_labels, facet_labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
x_position, y_position	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
x_sec_axis, y_sec_axis	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
x_symmetric, y_symmetric	TRUE or FALSE of whether a symmetric scale.
x_transform, y_transform, col_transform	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_prefix</code> (e.g. "log10").
col_drop, facet_drop	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
col_legend_ncol, col_legend_nrow	The number of columns and rows in a legend guide.
col_legend_rev	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.

<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> () may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol</code> , <code>facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>facet_space</code>	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  gg_smooth(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
    se = TRUE,
    blend = "multiply",
  )
```



```
data.frame(year = 1875:1972, level = as.vector(LakeHuron)) |>
  mutate(level_min = level - 1, level_max = level + 1) |>
  gg_smooth(
    stat = "identity",
    x = year,
    y = level,
    ymin = level_min,
    ymax = level_max,
    blend = "multiply",
    se = TRUE,
    x_labels = \(x) x,
  )
```

gg_step

Step ggplot

Description

Create a step plot with a wrapper around `ggplot2::ggplot() + geom_step()`.

Usage

```
gg_step(
  data = NULL,
  ...,
  stat = "identity",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
  ymax = NULL,
  yend = NULL,
  z = NULL,
  col = NULL,
  facet = NULL,
  facet2 = NULL,
```

```
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,  
facet_scales = "fixed",
```

```

facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .

<code>x_expand, y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".

facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

economics |>
  filter(date > lubridate::ymd("2010-01-01")) |>
  gg_step(
    x = date,
    y = unemploy,
    y_limits_include = 0,
    y_label = "Unemployment",
  )
```

gg_text

Text ggplot

Description

Create a text plot with a wrapper around `ggplot2::ggplot() + geom_text()`.

Usage

```
gg_text(
  data = NULL,
  ...,
  stat = "identity",
  position = "identity",
  coord = ggplot2::coord_cartesian(clip = "off"),
```

```
theme = NULL,  
theme_orientation = NULL,  
theme_axis_line_rm = NULL,  
theme_axis_ticks_rm = NULL,  
theme_panel_grid_rm = NULL,  
blend = NULL,  
x = NULL,  
xmin = NULL,  
xmax = NULL,  
xend = NULL,  
y = NULL,  
ymin = NULL,  
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,
```

```

col_label = NULL,
col_labels = NULL,
col_legend_ncol = NULL,
col_legend_nrow = NULL,
col_legend_rev = FALSE,
col_palette = NULL,
col_palette_na = NULL,
col_rescale = scales::rescale(),
col_steps = FALSE,
col_transform = NULL,
facet_axes = NULL,
facet_axis_labels = "margins",
facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

data	A data frame or tibble.
...	Other arguments passed to within a params list in layer().
stat	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
position	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a position_*() function that outputs a ggproto Position subclass object (e.g. ggplot2::position_identity()).
coord	A coordinate system. A coord_*() function that outputs a constructed ggproto Coord subclass object (e.g. ggplot2::coord_cartesian()).
theme	A ggplot2 theme (e.g. light_mode_t() or dark_mode_r()). (Or a list that includes 1. a theme and 2. a ggplot2::labs() function. E.g. list(light_mode_r(), labs(colour = NU
theme_orientation	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
theme_axis_line_rm	TRUE or FALSE of whether to remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether to remove the relevant axis ticks per the theme_orientation of the plot.

<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand</code> , <code>y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include</code> , <code>y_limits_include</code> , <code>col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label</code> , <code>y_label</code> , <code>col_label</code>	Label for the axis or legend title. Use + <code>ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels</code> , <code>y_labels</code> , <code>col_labels</code> , <code>facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position</code> , <code>y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis</code> , <code>y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric</code> , <code>y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform</code> , <code>y_transform</code> , <code>col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_prefix</code> (e.g. "log10").
<code>col_drop</code> , <code>facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol</code> , <code>col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.

col_palette	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
col_palette_na	A hex code (or name) for the colour of NA values.
col_rescale	For a continuous variable, a <code>scales::rescale()</code> function.
col_steps	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
facet_axes	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> () may be needed.
facet_axis_labels	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)

set_blanket()

bind_rows(
  mtcars |> slice_min(order_by = mpg),
  mtcars |> slice_max(order_by = mpg)
) |>
tibble::rownames_to_column("themel") |>
gg_text(
  x = themel,
  y = mpg,
  label = themel,
```

```
y_limits_include = 0,  
y_label = "Miles per gallon",  
col_palette = c(orange, "white", teal),  
)
```

gg_tile

Tile ggplot

Description

Create a tile plot with a wrapper around `ggplot2::ggplot() + geom_tile()`.

Usage

```
gg_tile(  
  data = NULL,  
  ...,  
  stat = "identity",  
  position = "identity",  
  coord = ggplot2::coord_cartesian(clip = "off"),  
  theme = NULL,  
  theme_orientation = NULL,  
  theme_axis_line_rm = NULL,  
  theme_axis_ticks_rm = NULL,  
  theme_panel_grid_rm = NULL,  
  blend = NULL,  
  x = NULL,  
  xmin = NULL,  
  xmax = NULL,  
  xend = NULL,  
  y = NULL,  
  ymin = NULL,  
  ymax = NULL,  
  yend = NULL,  
  z = NULL,  
  col = NULL,  
  facet = NULL,  
  facet2 = NULL,  
  group = NULL,  
  subgroup = NULL,  
  label = NULL,  
  text = NULL,  
  sample = NULL,  
  mapping = NULL,  
  x_breaks = NULL,  
  x_breaks_n = NULL,
```

```
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",  
facet_drop = FALSE,  
facet_labels = NULL,  
facet_layout = NULL,  
facet_ncol = NULL,  
facet_nrow = NULL,  
facet_scales = "fixed",  
facet_space = "fixed",  
title = NULL,  
subtitle = NULL,  
caption = NULL,  
label_case = NULL  
)
```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a params list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*()</code> function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*()</code> function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NULL))</code>).
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.
<code>x_breaks</code> , <code>y_breaks</code> , <code>col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
<code>x_breaks_n</code> , <code>y_breaks_n</code> , <code>col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand</code> , <code>y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include</code> , <code>y_limits_include</code> , <code>col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. 0). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label</code> , <code>y_label</code> , <code>col_label</code>	Label for the axis or legend title. Use + <code>ggplot2::labs(... = NULL)</code> for no title.

<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_prefix</code> (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*()</code> function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes + <code>*_theme_*</code> may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".
<code>facet_layout</code>	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or <code>facet2</code>) argument is provided, then defaults to "wrap". If NULL and both <code>facet</code> and <code>facet2</code> arguments are provided, defaults to "grid".
<code>facet_ncol, facet_nrow</code>	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
<code>facet_scales</code>	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>facet_space</code>	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
<code>title</code>	Title string.
<code>subtitle</code>	Subtitle string.
<code>caption</code>	Caption title string.
<code>label_case</code>	A function to format the label of unlabelled variables. Defaults to <code>snakecase::to_sentence_case</code> .

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  group_by(species, sex) |>
  summarise(across(flipper_length_mm, \(x) mean(x, na.rm = TRUE))) |>
  gg_tile(
    x = sex,
    y = species,
    col = flipper_length_mm,
  )
```

gg_violin

Violin ggplot

Description

Create a violin plot with a wrapper around `ggplot2::ggplot() + geom_violin()`.

Usage

```
gg_violin(
  data = NULL,
  ...,
  stat = "ydensity",
  position = "dodge",
  coord = ggplot2::coord_cartesian(clip = "off"),
  theme = NULL,
  theme_orientation = NULL,
  theme_axis_line_rm = NULL,
  theme_axis_ticks_rm = NULL,
  theme_panel_grid_rm = NULL,
  blend = NULL,
  x = NULL,
  xmin = NULL,
  xmax = NULL,
  xend = NULL,
  y = NULL,
  ymin = NULL,
```

```
ymax = NULL,  
yend = NULL,  
z = NULL,  
col = NULL,  
facet = NULL,  
facet2 = NULL,  
group = NULL,  
subgroup = NULL,  
label = NULL,  
text = NULL,  
sample = NULL,  
mapping = NULL,  
x_breaks = NULL,  
x_breaks_n = NULL,  
x_expand = NULL,  
x_limits_include = NULL,  
x_label = NULL,  
x_labels = NULL,  
x_position = "bottom",  
x_sec_axis = ggplot2::waiver(),  
x_symmetric = NULL,  
x_transform = NULL,  
y_breaks = NULL,  
y_breaks_n = NULL,  
y_expand = NULL,  
y_limits_include = NULL,  
y_label = NULL,  
y_labels = NULL,  
y_position = "left",  
y_sec_axis = ggplot2::waiver(),  
y_symmetric = NULL,  
y_transform = NULL,  
col_breaks = NULL,  
col_breaks_n = 5,  
col_drop = FALSE,  
col_limits_include = NULL,  
col_label = NULL,  
col_labels = NULL,  
col_legend_ncol = NULL,  
col_legend_nrow = NULL,  
col_legend_rev = FALSE,  
col_palette = NULL,  
col_palette_na = NULL,  
col_rescale = scales::rescale(),  
col_steps = FALSE,  
col_transform = NULL,  
facet_axes = NULL,  
facet_axis_labels = "margins",
```

```

facet_drop = FALSE,
facet_labels = NULL,
facet_layout = NULL,
facet_ncol = NULL,
facet_nrow = NULL,
facet_scales = "fixed",
facet_space = "fixed",
title = NULL,
subtitle = NULL,
caption = NULL,
label_case = NULL
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>...</code>	Other arguments passed to within a <code>params</code> list in <code>layer()</code> .
<code>stat</code>	A statistical transformation to use on the data. A snakecase character string of a ggproto Stat subclass object minus the Stat prefix (e.g. "identity").
<code>position</code>	A position adjustment. A snakecase character string of a ggproto Position subclass object minus the Position prefix (e.g. "identity"), or a <code>position_*</code> () function that outputs a ggproto Position subclass object (e.g. <code>ggplot2::position_identity()</code>).
<code>coord</code>	A coordinate system. A <code>coord_*</code> () function that outputs a constructed ggproto Coord subclass object (e.g. <code>ggplot2::coord_cartesian()</code>).
<code>theme</code>	A ggplot2 theme (e.g. <code>light_mode_t()</code> or <code>dark_mode_r()</code>). (Or a list that includes 1. a theme and 2. a <code>ggplot2::labs()</code> function. E.g. <code>list(light_mode_r(), labs(colour = NU</code>
<code>theme_orientation</code>	The orientation of plot, which affects the theme components that are removed. Either "x" or "y".
<code>theme_axis_line_rm</code>	TRUE or FALSE of whether to remove the relevant axis line per the <code>theme_orientation</code> of the plot.
<code>theme_axis_ticks_rm</code>	TRUE or FALSE of whether to remove the relevant axis ticks per the <code>theme_orientation</code> of the plot.
<code>theme_panel_grid_rm</code>	TRUE or FALSE of whether to remove the relevant panel grid per the <code>theme_orientation</code> of the plot.
<code>blend</code>	The blending mode per <code>ggblend::blend()</code> (e.g. "multiply").
<code>x</code> , <code>xmin</code> , <code>xmax</code> , <code>xend</code> , <code>y</code> , <code>ymin</code> , <code>ymax</code> , <code>yend</code> , <code>z</code> , <code>col</code> , <code>facet</code> , <code>facet2</code> , <code>group</code> , <code>subgroup</code> , <code>label</code> , <code>text</code> , <code>sample</code>	An unquoted aesthetic variable.
<code>mapping</code>	A set of additional aesthetic mappings in <code>ggplot2::aes()</code> . Intended primarily for non-supported aesthetics (e.g. <code>shape</code> , <code>linetype</code> , <code>linewidth</code> , or <code>size</code>), but can also be used for delayed evaluation etc.

<code>x_breaks, y_breaks, col_breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
<code>x_breaks_n, y_breaks_n, col_breaks_n</code>	A number of desired breaks for when <code>*_breaks = NULL</code> .
<code>x_expand, y_expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>x_limits_include, y_limits_include, col_limits_include</code>	For a continuous variable, any values that the limits should encompass (e.g. <code>0</code>). For a discrete scale, manipulate the data instead with <code>forcats::fct_expand</code> .
<code>x_label, y_label, col_label</code>	Label for the axis or legend title. Use <code>+ ggplot2::labs(... = NULL)</code> for no title.
<code>x_labels, y_labels, col_labels, facet_labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*</code> ()), or a vector of labels. (Note this must be named for <code>facet_labels</code>).
<code>x_position, y_position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top"). If using <code>y_position = "top"</code> with a <code>*_theme_*</code> theme, add <code>caption = ""</code> or <code>caption = "\n"</code> .
<code>x_sec_axis, y_sec_axis</code>	A secondary axis with <code>ggplot2::dup_axis()</code> or <code>ggplot2::sec_axis()</code> .
<code>x_symmetric, y_symmetric</code>	TRUE or FALSE of whether a symmetric scale.
<code>x_transform, y_transform, col_transform</code>	For a continuous scale, a transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_*</code> prefix (e.g. "log10").
<code>col_drop, facet_drop</code>	For a discrete variable, FALSE or TRUE of whether to drop unused levels.
<code>col_legend_ncol, col_legend_nrow</code>	The number of columns and rows in a legend guide.
<code>col_legend_rev</code>	TRUE or FALSE of whether to reverse the elements of a legend guide. Defaults to FALSE.
<code>col_palette</code>	A character vector of hex codes (or names) or a <code>scales::pal_*</code> () function.
<code>col_palette_na</code>	A hex code (or name) for the colour of NA values.
<code>col_rescale</code>	For a continuous variable, a <code>scales::rescale()</code> function.
<code>col_steps</code>	For a continuous variable, TRUE or FALSE of whether to colour in steps. Defaults to FALSE.
<code>facet_axes</code>	Whether to add interior axes and ticks with "margins", "all", "all_x", or "all_y". Sometimes <code>+ *_theme_*</code> () may be needed.
<code>facet_axis_labels</code>	Whether to add interior axis labels with "margins", "all", "all_x", or "all_y".

facet_layout	Whether the layout is to be "wrap" or "grid". If NULL and a single facet (or facet2) argument is provided, then defaults to "wrap". If NULL and both facet and facet2 arguments are provided, defaults to "grid".
facet_ncol, facet_nrow	The number of columns and rows of facet panels. Only applies to a facet layout of "wrap".
facet_scales	Whether facet scales should be "fixed" across facets, "free" in both directions, or free in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
facet_space	When the facet scales are <i>not</i> "fixed", whether facet space should be "fixed" across facets, "free" to be proportional in both directions, or free to be proportional in just one direction (i.e. "free_x" or "free_y"). Defaults to "fixed".
title	Title string.
subtitle	Subtitle string.
caption	Caption title string.
label_case	A function to format the label of unlabelled variables. Defaults to snakecase::to_sentence_case.

Value

A ggplot object.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  tidyr::drop_na(sex) |>
  gg_violin(
    x = species,
    y = body_mass_g,
    col = sex,
  )
```

grey

A grey colour

Description

A grey colour.

Usage

```
grey
```

Value

A character vector.

Examples

```
scales::show_col(grey)
```

guides_shape_grey *Guides for legend element colour*

Description

Guides to over-ride legend elements with a grey colour

- `guides_shape_grey()` for shape
- `guides_linewidth_grey()` for linewidth
- `guides_size_grey()` for size.

Usage

```
guides_shape_grey(colour = grey, ...)
```

```
guides_linewidth_grey(colour = grey, ...)
```

```
guides_size_grey(colour = grey, ...)
```

Arguments

`colour` A default hex code to override the colour of the legend elements. Note, the "fill" inherits from this argument. Defaults to grey.

`...` Other arguments passed to `ggplot2::guide_legend()`.

Value

A ggplot guides.

Examples

```
library(dplyr)
library(tidyr)
library(ggplot2)
library(palmerpenguins)

set_blanket()

penguins |>
  drop_na() |>
  gg_jitter(
    x = species,
    y = flipper_length_mm,
    col = island,
    mapping = aes(shape = sex),
  ) +
  guides_shape_grey()
```

jumble

The jumble palette

Description

A discrete palette that is relatively colour-blind safe.

Usage

```
jumble
teal
orange
navy
red
pink
purple
```

Value

A character vector.

Examples

```
colorspace::swatchplot(c(jumble, grey), cvd = TRUE)
```

label_every_nth	<i>Label every nth element</i>
-----------------	--------------------------------

Description

Label every nth element in a vector, and replace the rest with "".

Usage

```
label_every_nth(n = 2, offset = 0, ...)
```

Arguments

n	The increment of elements to hold as is. Defaults to 2.
offset	An offset for which element to first hold. Defaults to 0. Possible values are -1 to (n - 2)
...	If numeric, arguments passed to the <code>scales::comma</code> function. Otherwise, arguments passed to <code>format</code> .

Value

A labelling function

Examples

```
label_every_nth()(scales::comma(seq(1000, 5000, 1000)))
label_every_nth()(lubridate::ymd(c("2021-01-01", "2022-01-01", "2023-01-01", "2024-01-01")))
label_every_nth()(LETTERS[1:12])

library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  mutate(across(sex, \(x) stringr::str_to_sentence(x))) |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
    col = sex,
    x_labels = label_every_nth(),
    y_labels = label_every_nth(),
  )
```

lightness	<i>Mode colour and linewidth defaults</i>
-----------	---

Description

lightness and darkness are vectors of 3 colours used in the *_theme_* themes for the for the text, axis.line (and axis.ticks), panel.grid, panel.background and plot.background etc.

linewidth is a vector of 2 integers used in the *_theme_* themes for the linewidth of the axis.line (axis.ticks and legend.ticks) and panel.grid theme elements.

Usage

lightness

darkness

Value

A character vector.

Examples

```
scales::show_col(c(lightness, darkness), ncol = 3)
```

light_mode_r	<i>Light mode theme family</i>
--------------	--------------------------------

Description

A dark mode family of functions:

- light_mode_r() with legend on right
- light_mode_t() with legend on top
- light_mode_b() with legend on bottom

Usage

```
light_mode_r(
  ...,
  base_size = 11,
  base_family = "",
  base_colour = "#121B24FF",
  axis_line_colour = "#121B24FF",
  axis_line_linewidth = 0.25,
  axis_ticks_colour = axis_line_colour,
```

```
axis_ticks_linewidth = axis_line_linewidth,  
axis_ticks_length = grid::unit(11/3, "pt"),  
panel_grid_colour = "#F6F8FAFF",  
panel_grid_linewidth = 1.33,  
panel_background_fill = "#FFFFFF",  
plot_background_fill = "#FFFFFF",  
legend_axis_line_colour = plot_background_fill,  
legend_axis_line_linewidth = axis_line_linewidth,  
legend_background_fill = plot_background_fill,  
legend_key_fill = plot_background_fill,  
legend_ticks_colour = legend_axis_line_colour,  
legend_ticks_linewidth = legend_axis_line_linewidth,  
legend_ticks_length = ggplot2::rel(c(0.175, 0))  
)
```

```
light_mode_t(  
  ...,  
  base_size = 11,  
  base_family = "",  
  base_colour = "#121B24FF",  
  axis_line_colour = "#121B24FF",  
  axis_line_linewidth = 0.25,  
  axis_ticks_colour = axis_line_colour,  
  axis_ticks_linewidth = axis_line_linewidth,  
  axis_ticks_length = grid::unit(11/3, "pt"),  
  panel_grid_colour = "#F6F8FAFF",  
  panel_grid_linewidth = 1.33,  
  panel_background_fill = "#FFFFFF",  
  plot_background_fill = "#FFFFFF",  
  legend_axis_line_colour = plot_background_fill,  
  legend_axis_line_linewidth = axis_line_linewidth,  
  legend_background_fill = plot_background_fill,  
  legend_key_fill = plot_background_fill,  
  legend_ticks_colour = legend_axis_line_colour,  
  legend_ticks_linewidth = legend_axis_line_linewidth,  
  legend_ticks_length = ggplot2::rel(c(0.175, 0))  
)
```

```
light_mode_b(  
  ...,  
  base_size = 11,  
  base_family = "",  
  base_colour = "#121B24FF",  
  axis_line_colour = "#121B24FF",  
  axis_line_linewidth = 0.25,  
  axis_ticks_colour = axis_line_colour,  
  axis_ticks_linewidth = axis_line_linewidth,  
  axis_ticks_length = grid::unit(11/3, "pt"),
```

```

panel_grid_colour = "#F6F8FAFF",
panel_grid_linewidth = 1.33,
panel_background_fill = "#FFFFFF",
plot_background_fill = "#FFFFFF",
legend_axis_line_colour = plot_background_fill,
legend_axis_line_linewidth = axis_line_linewidth,
legend_background_fill = plot_background_fill,
legend_key_fill = plot_background_fill,
legend_ticks_colour = legend_axis_line_colour,
legend_ticks_linewidth = legend_axis_line_linewidth,
legend_ticks_length = ggplot2::rel(c(0.175, 0))
)

```

Arguments

...	Provided to require argument naming, support trailing commas etc.
base_size	The base size of the text theme element. Defaults to 11.
base_family	The base family of the text theme element. Defaults to "".
base_colour	The base colour of the text theme element.
axis_line_colour	The colour of the axis.line theme element.
axis_line_linewidth	The linewidth of the axis.line theme element.
axis_ticks_colour	The colour of the axis.ticks theme element.
axis_ticks_linewidth	The linewidth of the axis.ticks theme element.
axis_ticks_length	The length of the axis.ticks.length theme element.
panel_grid_colour	The colour of the panel.grid theme element.
panel_grid_linewidth	The linewidth of the panel.grid theme element.
panel_background_fill	The fill (and colour) of the panel.background theme element.
plot_background_fill	The fill (and colour) of the plot.background theme element.
legend_axis_line_colour	The colour of the legend.axis.line theme element.
legend_axis_line_linewidth	The linewidth of the legend.axis.line theme element.
legend_background_fill	The fill (and colour) of the legend.background theme element.
legend_key_fill	The fill (and colour) of the legend.key theme element.

legend_ticks_colour
The colour of the legend.ticks theme element.

legend_ticks_linewidth
The linewidth of the legend.ticks theme element.

legend_ticks_length
The legend.ticks.length theme element.

Value

A ggplot theme.

Examples

```
library(palmerpenguins)
library(ggplot2)

set_blanket()

penguins |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
    mode = light_mode_r()
  )

penguins |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
    mode = light_mode_t()
  )

penguins |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
    col = species,
    mode = light_mode_b()
  )
```

scale_x_symmetric *Symmetric x continuous scale*

Description

Create a symmetric continuous x scale for ggplot2 plots. The scale ensures that limits set to the range of breaks with zero expand (where `symmetric = TRUE`). Note this scale should only be used in plots with geoms with `stat = "identity"`.

Usage

```
scale_x_symmetric(
  data = NULL,
  x = NULL,
  ...,
  breaks = NULL,
  breaks_n = 6,
  expand = NULL,
  expand_limits = NULL,
  labels = NULL,
  position = "bottom",
  sec_axis = ggplot2::waiver(),
  transform = "identity",
  symmetric = TRUE
)
```

Arguments

<code>data</code>	A data frame or tibble.
<code>x</code>	An unquoted variable.
<code>...</code>	Provided to force user argument naming etc.
<code>breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*()</code>), or a vector of breaks.
<code>breaks_n</code>	If <code>breaks = NULL</code> , the desired number of breaks.
<code>expand</code>	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
<code>expand_limits</code>	Any values that the limits should encompass (e.g. <code>0</code>).
<code>labels</code>	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels.
<code>position</code>	The position of the axis (i.e. "left", "right", "bottom" or "top").
<code>sec_axis</code>	A secondary axis created with <code>ggplot2::sec_axis()</code> or <code>ggplot2::dup_axis()</code> .
<code>transform</code>	A transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
<code>symmetric</code>	TRUE or FALSE of whether a symmetric scale.

Value

A `ggplot2` continuous x scale.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()
```

```

penguins |>
  ggplot() +
  geom_jitter(aes(x = body_mass_g, y = species, colour = species)) +
  scale_x_symmetric(penguins, body_mass_g) +
  theme(axis.line.x = element_blank()) +
  theme(axis.ticks.x = element_blank()) +
  theme(panel.grid.major.y = element_blank()) +
  theme(axis.ticks.y = element_blank()) +
  coord_cartesian(clip = "off") +
  labs(x = "Body mass g", y = "Species", colour = "Species")

```

scale_y_symmetric *Symmetric y continuous scale*

Description

Create a symmetric continuous y scale for ggplot2 plots. The scale ensures that limits set to the range of breaks with zero expand (where `symmetric = TRUE`). Note this scale should only be used in plots with geoms with `stat = "identity"`. Symmetric y continuous scale

Usage

```

scale_y_symmetric(
  data = NULL,
  y = NULL,
  ...,
  breaks = NULL,
  breaks_n = 6,
  expand = NULL,
  expand_limits = NULL,
  labels = NULL,
  position = "left",
  sec_axis = ggplot2::waiver(),
  transform = "identity",
  symmetric = TRUE
)

```

Arguments

<code>data</code>	A data frame or tibble.
<code>y</code>	An unquoted variable.
<code>...</code>	Provided to force user argument naming etc.
<code>breaks</code>	A <code>scales::breaks_*</code> function (e.g. <code>scales::breaks_*</code> ()), or a vector of breaks.
<code>breaks_n</code>	If <code>breaks = NULL</code> , the desired number of breaks.

expand	Padding to the limits with the <code>ggplot2::expansion()</code> function, or a vector of length 2 (e.g. <code>c(0, 0)</code>).
expand_limits	Any values that the limits should encompass (e.g. <code>0</code>).
labels	A function that takes the breaks as inputs (e.g. <code>\(x) stringr::str_to_sentence(x)</code> or <code>scales::label_*()</code>), or a vector of labels.
position	The position of the axis (i.e. "left", "right", "bottom" or "top").
sec_axis	A secondary axis created with <code>ggplot2::sec_axis()</code> or <code>ggplot2::dup_axis()</code> .
transform	A transformation object (e.g. <code>scales::transform_log10()</code>) or character string of this minus the <code>transform_</code> prefix (e.g. "log10").
symmetric	TRUE or FALSE of whether a symmetric scale.

Value

A ggplot2 continuous y scale.

Examples

```
library(ggplot2)
library(dplyr)
library(palmerpenguins)

set_blanket()

penguins |>
  ggplot() +
  geom_point(aes(x = flipper_length_mm, y = body_mass_g, colour = species)) +
  scale_y_symmetric(penguins, body_mass_g) +
  theme(axis.line.y = element_blank()) +
  theme(axis.ticks.y = element_blank()) +
  theme(panel.grid.major.x = element_blank()) +
  coord_cartesian(clip = "off") +
  labs(x = "Flipper length mm", y = "Body mass g", colour = "Species")
```

set_blanket

Set the style

Description

Set the style by setting:

1. the geom defaults, including the colour (and fill) of geoms
2. the colour (and fill) palettes (i.e. discrete, continuous and ordinal)
3. the theme, and how/what side-effects are to be applied
4. the function to apply to a unspecified/unlabelled `x_label`, `y_label`, `col_label` etc.

`ggplot2::update_geom_defaults()` can be used to further fine-tune geom defaults.

Usage

```

set_blanket(
  ...,
  colour = "#357BA2FF",
  col_palette_d = jumble,
  col_palette_c = viridisLite::mako(n = 9, direction = -1),
  col_palette_o = scales::pal_viridis(option = "G", direction = -1),
  col_palette_na_d = "#CDC5BFFF",
  col_palette_na_c = "#988F88FF",
  col_palette_na_o = "#988F88FF",
  theme = light_mode_r(),
  theme_orientation = NULL,
  theme_axis_line_rm = TRUE,
  theme_axis_ticks_rm = TRUE,
  theme_panel_grid_rm = TRUE,
  label_case = snakecase::to_sentence_case
)

```

Arguments

...	Provided to require argument naming, support trailing commas etc.
colour	For most geoms, a default hex code for the colour of geoms (i.e. geoms other than "text", "label", "hline", and "vline"). Note, the "fill" inherits from this argument.
col_palette_d	For a discrete scale, a character vector of hex codes.
col_palette_c	For a continuous scale, a character vector of hex codes.
col_palette_o	For an ordinal scale, a scales::pal_*() function.
col_palette_na_d	For a discrete scale, a hex code.
col_palette_na_c	For a continuous scale, a hex code.
col_palette_na_o	For an ordinal scale, a hex code.
theme	A ggplot2 theme (e.g. light_mode_t() or dark_mode_r()).
theme_orientation	The orientation of plot, which affects the theme components that can be removed by the gg_* function. Either "x" or "y". Defaults to NULL, which lets the gg_* function guess it based on the data.
theme_axis_line_rm	TRUE or FALSE of whether the gg_* function should remove the relevant axis line per the theme_orientation of the plot.
theme_axis_ticks_rm	TRUE or FALSE of whether the gg_* function should remove the relevant axis ticks per the theme_orientation of the plot.

`theme_panel_grid_rm` TRUE or FALSE of whether the `gg_*` function should remove the relevant panel grid per the `theme_orientation` of the plot.

`label_case` A function to apply to a unspecified/unlabelled `x_label`, `y_label`, `col_label` etc. Defaults to `snakecase::to_sentence_case`.

Value

A globally set style.

Examples

```
library(ggplot2)
library(ggblanket)
library(palmerpenguins)

set_blanket(
  theme = dark_mode_r(),
  colour = "#E7298AFF",
  col_palette_d = c("#1B9E77FF", "#D95F02FF", "#7570b3FF", "#E7298AFF",
                    "#66A61EFF", "#E6AB02FF", "#A6761DFF", "#666666FF"),
)

penguins |>
  gg_point(
    x = flipper_length_mm,
    y = body_mass_g,
  )

penguins |>
  gg_histogram(
    x = flipper_length_mm,
    col = species,
  )
```

Index

- * **datasets**
 - blue, [7](#)
 - grey, [178](#)
 - jumble, [180](#)
 - lightness, [182](#)
- aes_contrast, [3](#)
- annotate_axis_line, [4](#)
- bind_each_all, [6](#)
- blue, [7](#)
- dark_mode_b (dark_mode_r), [8](#)
- dark_mode_r, [8](#)
- dark_mode_r(), [13](#), [18](#), [22](#), [26](#), [31](#), [35](#), [40](#), [44](#), [48](#), [53](#), [57](#), [61](#), [66](#), [70](#), [75](#), [79](#), [83](#), [88](#), [92](#), [97](#), [101](#), [105](#), [110](#), [114](#), [119](#), [123](#), [128](#), [132](#), [136](#), [141](#), [145](#), [150](#), [154](#), [158](#), [163](#), [167](#), [172](#), [176](#), [189](#)
- dark_mode_t (dark_mode_r), [8](#)
- darkness (lightness), [182](#)
- geom_area(), [11](#)
- geom_bar(), [16](#)
- geom_bin_2d(), [20](#)
- geom_blank(), [24](#)
- geom_boxplot(), [29](#)
- geom_col(), [33](#)
- geom_contour(), [38](#)
- geom_contour_filled(), [42](#)
- geom_crossbar(), [46](#)
- geom_density(), [51](#)
- geom_density_2d(), [55](#)
- geom_density_2d_filled(), [59](#)
- geom_errorbar(), [64](#)
- geom_freqpoly(), [68](#)
- geom_function(), [73](#)
- geom_hex(), [77](#)
- geom_histogram(), [81](#)
- geom_jitter(), [86](#)
- geom_label(), [90](#)
- geom_line(), [95](#)
- geom_linerange(), [99](#)
- geom_path(), [103](#)
- geom_point(), [108](#)
- geom_pointrange(), [112](#)
- geom_polygon(), [117](#)
- geom_qq(), [121](#)
- geom_quantile(), [126](#)
- geom_raster(), [130](#)
- geom_rect(), [134](#)
- geom_ribbon(), [139](#)
- geom_rug(), [143](#)
- geom_segment(), [148](#)
- geom_sf(), [152](#)
- geom_smooth(), [156](#)
- geom_step(), [161](#)
- geom_text(), [165](#)
- geom_tile(), [170](#)
- geom_violin(), [174](#)
- gg_area, [11](#)
- gg_bar, [16](#)
- gg_bin_2d, [20](#)
- gg_blanket, [24](#)
- gg_boxplot, [29](#)
- gg_col, [33](#)
- gg_contour, [38](#)
- gg_contour_filled, [42](#)
- gg_crossbar, [46](#)
- gg_density, [51](#)
- gg_density_2d, [55](#)
- gg_density_2d_filled, [59](#)
- gg_errorbar, [64](#)
- gg_freqpoly, [68](#)
- gg_function, [73](#)
- gg_hex, [77](#)
- gg_histogram, [81](#)
- gg_jitter, [86](#)
- gg_label, [90](#)

- gg_line, 95
- gg_linerange, 99
- gg_path, 103
- gg_point, 108
- gg_pointrange, 112
- gg_polygon, 117
- gg_qq, 121
- gg_quantile, 126
- gg_raster, 130
- gg_rect, 134
- gg_ribbon, 139
- gg_rug, 143
- gg_segment, 148
- gg_sf, 152
- gg_smooth, 156
- gg_step, 161
- gg_text, 165
- gg_tile, 170
- gg_violin, 174
- ggblend::blend(), 14, 18, 22, 27, 31, 35, 40, 44, 49, 53, 57, 62, 66, 70, 75, 79, 83, 88, 92, 97, 101, 106, 110, 114, 119, 124, 128, 132, 137, 141, 146, 150, 154, 159, 163, 168, 172, 176
- ggplot2::aes, 3
- ggplot2::aes(), 14, 18, 22, 27, 31, 35, 40, 44, 49, 53, 58, 62, 66, 71, 75, 79, 84, 88, 92, 97, 101, 106, 110, 114, 119, 124, 128, 132, 137, 141, 146, 150, 154, 159, 163, 168, 172, 176
- ggplot2::coord_cartesian(), 13, 18, 22, 26, 31, 35, 40, 44, 48, 53, 57, 61, 66, 70, 75, 79, 83, 88, 92, 97, 101, 105, 110, 114, 119, 123, 128, 132, 136, 141, 145, 150, 154, 158, 163, 167, 172, 176
- ggplot2::dup_axis(), 14, 19, 23, 27, 32, 36, 41, 45, 49, 54, 58, 62, 67, 71, 76, 80, 84, 89, 93, 98, 102, 106, 111, 115, 120, 124, 129, 133, 137, 142, 146, 151, 155, 159, 164, 168, 173, 177, 186, 188
- ggplot2::expansion(), 14, 18, 23, 27, 31, 36, 40, 45, 49, 53, 58, 62, 66, 71, 75, 79, 84, 88, 93, 97, 102, 106, 110, 115, 119, 124, 128, 133, 137, 141, 146, 150, 155, 159, 164, 168, 172, 177, 186, 188
- ggplot2::ggplot(), 11, 16, 20, 24, 29, 33, 38, 42, 46, 51, 55, 59, 64, 68, 73, 77, 81, 86, 90, 95, 99, 103, 108, 112, 117, 121, 126, 130, 134, 139, 143, 148, 152, 156, 161, 165, 170, 174
- ggplot2::guide_legend(), 179
- ggplot2::labs(), 13, 18, 22, 26, 31, 35, 40, 44, 48, 53, 57, 61, 66, 70, 75, 79, 83, 88, 92, 97, 101, 105, 110, 114, 119, 123, 128, 132, 136, 141, 145, 150, 154, 158, 163, 167, 172, 176
- ggplot2::sec_axis(), 14, 19, 23, 27, 32, 36, 41, 45, 49, 54, 58, 62, 67, 71, 76, 80, 84, 89, 93, 98, 102, 106, 111, 115, 120, 124, 129, 133, 137, 142, 146, 151, 155, 159, 164, 168, 173, 177, 186, 188
- ggplot2::update_geom_defaults(), 188
- grey, 178
- guides_linewidth_grey (guides_shape_grey), 179
- guides_shape_grey, 179
- guides_size_grey (guides_shape_grey), 179
- jumble, 180
- label_every_nth, 181
- light_mode_b (light_mode_r), 182
- light_mode_r, 182
- light_mode_t (light_mode_r), 182
- light_mode_t(), 13, 18, 22, 26, 31, 35, 40, 44, 48, 53, 57, 61, 66, 70, 75, 79, 83, 88, 92, 97, 101, 105, 110, 114, 119, 123, 128, 132, 136, 141, 145, 150, 154, 158, 163, 167, 172, 176, 189
- lightness, 182
- navy (jumble), 180
- orange (jumble), 180
- pink (jumble), 180
- purple (jumble), 180
- red (jumble), 180
- scale_x_symmetric, 185
- scale_y_symmetric, 187

scales::transform_log10(), [14](#), [19](#), [23](#), [27](#),
[32](#), [36](#), [41](#), [45](#), [49](#), [54](#), [58](#), [62](#), [67](#), [71](#),
[76](#), [80](#), [84](#), [89](#), [93](#), [98](#), [102](#), [106](#), [111](#),
[115](#), [120](#), [124](#), [129](#), [133](#), [137](#), [142](#),
[146](#), [151](#), [155](#), [159](#), [164](#), [168](#), [173](#),
[177](#), [186](#), [188](#)
set_blanket, [188](#)
teal (jumble), [180](#)