

Package ‘LARF’

October 12, 2022

Type Package

Title Local Average Response Functions for Instrumental Variable
Estimation of Treatment Effects

Version 1.4

Date 2016-07-25

Author Weihua An and Xuefu Wang, Indiana University Bloomington

Maintainer Weihua An <weihuaan@indiana.edu>

Description Provides instrumental variable estimation of treatment effects when both the endogenous treatment and its instrument are binary. Applicable to both binary and continuous outcomes.

Imports Formula

License GPL-3

NeedsCompilation no

Repository CRAN

Date/Publication 2016-07-26 12:04:14

R topics documented:

c401k	2
cvlm	3
Generate.Powers	4
larf	4
larf.fit	7
npse	8
predict.larf	9
print.larf	10
summary.larf	11
vcov.larf	11

Index	13
--------------	-----------

c401k

c401k

Description

Cross-sectional data with 9,275 observations including 11 variables on eligibility for and participation in 401(k) along with income and demographic information.

Usage

```
data(c401k)
```

Format

```
pira participation in IRA, participation = 1
nettfa net family financial assets in $1000
p401k participation in 401(k), participation = 1
e401k eligibility for 401(k), eligible = 1
inc income
incsq income square
marr marital status, married = 1
male sex, male = 1
age age
agesq age square
fsize family size
```

Details

An exemplary data to illustrate the usage of `larf`. The data includes both a binary outcome (`pira`) and a continuous outcome (`nettfa`). The treatment is participation in 401k, `p401k`. Eligibility for 401(k), `e401k`, is used as an instrument for `p401k`.

Source

The Wooldridge Data Sets (Wooldridge 2010), originally entitled "401ksubs.dta" in Stata format, available at <http://www.stata.com/texts/eacsap/>.

References

Wooldridge, Jeffrey M. 2010. *Econometric Analysis of Cross Section and Panel Data*. 2nd Edition. MIT Press.

See Also

[larf](#), [larf.fit](#)

Examples

```
data(c401k)
```

```
cvlm
```

Cross-validation of a Linear Regression Model

Description

Provides cross-validation of a linear regression model

Usage

```
cvlm(form.lm, data, m=10, seed = NULL)
```

Arguments

form.lm	formula of the regression model.
data	data including outcome and covaraites.
m	the number of folds to be used in cross-validation.
seed	random starting number used to replicate cross-validation.

Details

This function finds the optimal order of the covariates power series through cross-validation.

Value

sumres	Sum of residual squares divided by degree of freedom.
df	Degree of freedom which equals to the number of valid predictions minus the number of parameters.
m	the number of folds to be used in cross-validation.
seed	The random seed.

Note

In making the code, we adopted part of the CVlm in DAAG (Maindonald and Braun, 2015).
<https://cran.r-project.org/package=DAAG>

Author(s)

Weihua An, Departments of Sociology and Statistics, Indiana University Bloomington, <weihuaan@indiana.edu>.
Xuefu Wang, Department of Statistics, Indiana University Bloomington, <wangxuef@umail.iu.edu>.

See Also

[larf](#), [npse](#)

Generate.Powers	<i>Generating Powers Series of Variables</i>
-----------------	--

Description

Internal function used by [npse](#) to generate covariates power series.

Usage

```
Generate.Powers(X, lambda)
```

Arguments

X	covariates.
lambda	the maximal order of power series.

Author(s)

Weihua An, Departments of Statistics and Sociology, Indiana University Bloomington, <weihuaan@indiana.edu>. Xuefu Wang, Department of Statistics, Indiana University Bloomington, <wangxuef@umail.iu.edu>.

See Also

[larf](#), [npse](#)

larf	<i>Local Average Response Functions for Instrumental Variable Estimation of Treatment Effects</i>
------	---

Description

The function provides instrumental variable estimation of treatment effects when both the endogenous treatment and its instrument are binary. Applicable to both binary and continuous outcomes.

Usage

```
larf(formula, treatment, instrument, data, method = "LS",  
      AME = FALSE, optimizer = "Nelder-Mead", zProb = NULL)
```

Arguments

formula	specification of the outcome model in the form like either $y \sim x_1 + x_2$ or $y \sim X$ where X is a matrix containing all the covariates excluding the treatment. Also support multi-part formulas (Zeileis and Croissant, 2010). For example, $y + d \sim x_1 + x_2 \mid z$, where d represents the treatment and z the instrument.
treatment	A vector containing the binary treatment.
instrument	A vector containing the binary instrument for the endogenous treatment.
data	an optional data frame. If unspecified, the data will be taken from the working environment.
method	the estimation method to be used. The default is "LS", standing for least squares. "ML", standing for maximum likelihood, is an alternative.
AME	whether average marginal effects (AME) should be reported. The default is FALSE, in which case marginal effects at the means (MEM) are reported.
optimizer	the optimization algorithm for the ML method. It should be one of "Nelder-Mead", "BFGS", "CG", "L-BFGS-B", "SANN", or "Brent". See <code>optim</code> in R for more detail.
zProb	a vector containing the probability of receiving the treatment inducement (i.e., <code>instrument = 1</code>) that have been estimated by semiparametrical methods.

Details

`larf` is the high-level interface to the work-horse function `larf.fit`. A set of standard methods (including `print`, `summary`, `coef`, `vcov`, `fitted`, `resid`, `predict`) can be used to extract the corresponding information from a `larf` object.

The function provides instrumental variable estimation of treatment effects when both the endogenous treatment and its instrument (i.e., the treatment inducement) are binary. The method (Abadie, 2003) involves two steps. First, pseudo-weights are constructed from the probability of receiving the treatment inducement. By default the function estimates the probability by a Probit regression. But it also allows users to employ the probability that has been estimated by semiparametric methods. Second, the pseudo-weights are used to estimate the local average response function of the outcome conditional on the treatment and covariates. The function provides both least squares and maximum likelihood estimates of the conditional treatment effects.

Value

<code>coefficients</code>	Estimated coefficients.
<code>SE</code>	Standard errors of the estimated coefficients.
<code>MargEff</code>	Estimated marginal effects, available only for binary outcomes.
<code>MargStdErr</code>	Standard errors of the estimated marginal effects, available only for binary outcomes.
<code>vcov</code>	Variance covariance matrix of the estimated coefficients.
<code>fitted.values</code>	Predicted outcomes based on the estimated model. They are probabilities when the outcome is binary.

Note

We derived part of the code from the Matlab code written by Professor Alberto Abadie, available at <http://www.hks.harvard.edu/fs/aabadie/larf.html>. We thank Onur Altindag and Behzad Kianian for helpful suggestions on improving the computation.

Author(s)

Weihua An, Departments of Sociology and Statistics, Indiana University Bloomington, <weihuaan@indiana.edu>. Xuefu Wang, Department of Statistics, Indiana University Bloomington, <wangxuefu@mail.iu.edu>.

References

Abadie, Alberto. 2003. "Semiparametric Instrumental Variable Estimation of Treatment Response Models." *Journal of Econometrics* 113: 231-263.

An, Weihua and Xuefu Wang. 2016. "LARF: Instrumental Variable Estimation of Causal Effects through Local Average Response Functions." *Journal of Statistical Software* 71(1): 1-13.

Zeileis, Achim and Yves Croissant. 2010. "Extended Model Formulas in R: Multiple Parts and Multiple Responses." *Journal of Statistical Software* 34(1): 1-13. <http://www.jstatsoft.org/v34/i01/>.

See Also

[larf.fit, c401k](#)

Examples

```
data(c401k)
attach(c401k)

## Not run:
# Continuous outcome. Treatment effects of participation in 401(k)
# on net family financial assest
est1 <- larf(netffa ~ inc + age + agesq + marr + fsize, treatment = p401k,
instrument = e401k, data = c401k)
summary(est1)

# Nonparametric estimates of the probability of
# receiving the treatment inducement
library(mgcv)
firstStep <- gam(e401k ~ s(inc) + s(age) + s(agesq) + marr + s(fsize),
data=c401k, family=binomial(link = "probit"))
zProb <- firstStep$fitted
est2<- larf(netffa ~ inc + age + agesq + marr + fsize, treatment = p401k,
instrument = e401k, data = c401k, zProb = zProb)
summary(est2)

# Binary outcome. Treatment effects of participation in 401(k)
# on participation in IRA
est3 <- larf(pira ~ inc + age + agesq + marr + fsize, treatment = p401k,
instrument = e401k, data = c401k)
summary(est3)
```

```
## End(Not run)
```

`larf.fit`*Fitting the Local Average Response Function*

Description

It is the work-horse function for its high-level interface `larf`.

Usage

```
larf.fit(Y, X, D, Z, method, AME, optimizer, zProb)
```

Arguments

<code>Y</code>	a vector containing the outcome.
<code>X</code>	a matrix containing the covariates excluding the treatment.
<code>D</code>	a vector containing the binary treatment.
<code>Z</code>	a vector containing the binary instrument for the endogenous treatment.
<code>method</code>	the estimation method to be used. The default is "LS", standing for least squares. "ML", standing for maximum likelihood, is an alternative.
<code>AME</code>	whether average marginal effects (AME) should be reported. The default is FALSE, in which case marginal effects at the means (MEM) are reported.
<code>optimizer</code>	the optimization algorithm for the ML method. It should be one of "Nelder-Mead", "BFGS", "CG", "L-BFGS-B", "SANN", or "Brent". See <code>optim</code> in R for more detail.
<code>zProb</code>	a vector containing the probability of receiving the treatment inducement (i.e., <code>instrument = 1</code>) that have been estimated by semiparametrical methods.

Author(s)

Weihua An and Xuefu Wang, Departments of Sociology and Statistics, Indiana University Bloomington

See Also

[larf](#), [c401k](#)

npse

*Nonparametric Power Series Estimation***Description**

Use the optimal order of power series of covariates to predict outcome. The optimal order of power series is determined by cross-validation.

Usage

```
npse(formula, order = 3, m = 10, seed = NULL)
```

Arguments

formula	specification of the outcome model in the form like either $z \sim x_1 + x_2$ or $z \sim X$ where X is the covariate matrix.
order	the maximal order of power series to be used.
m	the number of folds to be used in cross-validation.
seed	random starting number used to replicate cross-validation.

Details

This function predicts the outcome based on the optimal order of covariates power series. The optimal order of the power series is determined by cross-validation. For example, it can be used to predict the probability of receiving treatment inducement based on covariates.

Value

fitted	Predicted outcomes based on the estimated model. They are probabilities when the outcome is binary.
Lambda	The optimal order of power series determined by cross-validation.
Data.opt	The data including z and the optimal covariates power series.
CV.Res	The residual sum of squares of the cross-validations.
seed	The random seed.

Author(s)

Weihua An, Departments of Sociology and Statistics, Indiana University Bloomington, <weihuaan@indiana.edu>. Xuefu Wang, Department of Statistics, Indiana University Bloomington, <wangxuef@umail.iu.edu>.

References

Abadie, Alberto. 2003. "Semiparametric Instrumental Variable Estimation of Treatment Response Models." *Journal of Econometrics* 113: 231-263.

See Also[larf](#), [larf.fit](#)**Examples**

```

data(c401k)
attach(c401k)

## Not run:
# binary outcome
Z <- c401k$e401k

# covariates
X <- as.matrix(c401k[,c("inc", "male", "fsize" )])

# get nonparametric power series estimation of the regression of Z on X
zp <- npse(Z~X, order = 5, m = 10, seed = 681)

# sum of residual squares of the cross-validations
zp$CV.Res

# the optimal order of the power series
zp$Lambda

# summary of the predictions based on the optimal power series
summary(zp$fitted)

## End(Not run)

```

predict.larf

Predictions Based on the Estimated LARF

Description

Predict new outcomes based on the model fitted by [larf](#).

Usage

```

## S3 method for class 'larf'
predict(object, newCov, newTreatment, ...)

```

Arguments

object	an object of class <code>larf</code> as fitted by larf .
newCov	A matrix containing the new covariates.
newTreatment	A vector containing the new binary treatment.
...	currently not used.

Details

Predicted outcomes are based on the estimated coefficients and new covariates and/or new treatment. The predicted outcomes are probabilities when the outcome is binary.

Value

predicted.values

The function returns a vector of the predicted outcomes.

Author(s)

Weihua An and Xuefu Wang, Departments of Statistics and Sociology, Indiana University Bloomington

See Also

[larf](#), [larf.fit](#)

print.larf

Print Results of the Estimated LARF

Description

Methods to display brief results of a [larf](#) object.

Usage

```
## S3 method for class 'larf'  
print(x, digits = 4, ...)
```

Arguments

x an object of class "larf" as fitted by [larf](#).
digits The number of significant digits to be printed in the reports of the results.
... currently not used.

Author(s)

Weihua An and Xuefu Wang, Departments of Statistics and Sociology, Indiana University Bloomington

See Also

[larf](#), [larf.fit](#)

summary.larf	<i>Summary of the Estimated LARF</i>
--------------	--------------------------------------

Description

Summary of an object in the [larf](#) class.

Usage

```
## S3 method for class 'larf'  
summary(object, ...)
```

Arguments

object	an object of class "larf" as fitted by larf .
...	currently not used.

Author(s)

Weihua An and Xuefu Wang, Departments of Statistics and Sociology, Indiana University Bloomington

See Also

[larf](#), [larf.fit](#)

vcov.larf	<i>Variance Covariance Matrix of the Parameters in the Estimated LARF</i>
-----------	---

Description

Methods to display the variance covariance matrix of the model parameters estimated by [larf](#).

Usage

```
## S3 method for class 'larf'  
vcov(object, ...)
```

Arguments

object	an object of class "larf" as fitted by larf .
...	currently not used.

Author(s)

Weihua An and Xuefu Wang, Departments of Statistics and Sociology, Indiana University Bloomington

See Also

[larf](#), [larf.fit](#)

Index

c401k, [2](#), [6](#), [7](#)

cvlm, [3](#)

Generate.Powers, [4](#)

larf, [2-4](#), [4](#), [5](#), [7](#), [9-12](#)

larf.fit, [2](#), [5](#), [6](#), [7](#), [9-12](#)

npse, [3](#), [4](#), [8](#)

predict.larf, [9](#)

print.larf, [10](#)

print.summary.larf (summary.larf), [11](#)

summary.larf, [11](#)

vcov.larf, [11](#)